



Mullen Circle Brand, Inc.

3514 W. Touhy Avenue
Skokie, IL 60076

Phone 847/676-1880

Fax 847/676-3748

Solutions@MullenOil.com

ELEVATOR HYDRAULIC OILS

Mullen Circle Brand **ELEVATOR HYDRAULIC OILS** enjoy an enviable reputation for high quality, reliable performance throughout the elevator industry. We attribute this to meticulous quality control on elevator lubricants formulated from the finest virgin mineral oils and the best available anti-wear additives. Superior performance also results from outstanding rust inhibition, oxidation resistance, and anti-foam properties.

TYPICAL PROPERTIES:

	<u>#32</u>	<u>#46</u>	<u>#68</u>	<u>#150</u>
Viscosity, SUS @ 100 F	160	240	350	800
Viscosity, Cst @ 40 C	32	46	68	150
Demulsibility	Pass	Pass	Pass	Pass
Pour Point, F	-20	-20	-20	-10
Pounds/Gallon	7.1	7.3	7.3	7.5
Color	Gold	Gold	Gold	Gold
Copper Corrosion, (3 Hrs. @ 210 F)	None	None	None	None
Steel Corrosion				
Distilled Water	Pass	Pass	Pass	Pass
Synthetic Seawater	Pass	Pass	Pass	Pass
Foam Test (Foam Height @ 10 Minutes)	None	None	None	None

...Providing Solutions To Industry Since 1912...

Cutting Fluids * Industrial Lubricants * Greases * Cleaners

The Information Given Herein Is Believed To Be Reliable, But No Guarantee Is Made Nor Liability Assumed.



Mullen Circle Brand, Inc.

3514 W. Touhy Avenue
Skokie, IL 60076

Phone 847/676-1880

Fax 847/676-3748

Solutions@MullenOil.com

#32AC ANTI-CHATTER ELEVATOR HYDRAULIC OIL

#32AC ANTI-CHATTER ELEVATOR HYDRAULIC OIL is a premium hydraulic oil for all hydraulic elevators. This unique product improves upon the natural lubricity of petroleum oil in order to reduce chattering and ensure smooth starts and stops. While critical for new installations, this oil can also be used to enhance the performance of existing hydraulic elevators.

#32AC ANTI-CHATTER ELEVATOR HYDRAULIC OIL incorporates new polymer technology to provide an ultrathin film of lubricity on all contacted parts. This film reduces friction dramatically while increasing the film strength of the oil. This results in lower oil temperatures, faster break-in times, fewer service calls, and a greater degree of customer satisfaction.

#32AC ANTI-CHATTER ELEVATOR HYDRAULIC OIL is completely compatible with Mullen Circle Brand's complete line of elevator hydraulic oils. All these oils are blended from the finest virgin petroleum oils and the proper type and amount of rust, oxidation, and wear inhibitors for elevator application.

TYPICAL PROPERTIES:

Viscosity, SUS @ 100 F	160
Viscosity, Cst @ 40 C	32
Demulsibility	Pass
Pour Point, F	-20
Pounds/Gallon	7.1
Color	Gold
Copper Corrosion, (3 Hrs. @ 210 F)	None
Steel Corrosion	
Distilled Water	Pass
Synthetic Seawater	Pass
Foam Test	None
(Foam Height @ 10 Minutes)	

...Providing Solutions To Industry Since 1912...

-18-

Cutting Fluids * Industrial Lubricants * Greases * Cleaners

The Information Given Herein Is Believed To Be Reliable, But No Guarantee Is Made Nor Liability Assumed.