

# EEZ PRODUCTS

## SYNLUBE CH

*Hydraulic & Compressor Oils*  
*Synthetic PAO/Ester*

*For More Info, Visit..*

[EEZProducts.com](http://EEZProducts.com)

*Foamy Cutting Fluid*  
*Tuf Tap 2-15-T*  
*Insted-A-Led*

*Micro Max*  
*Cool Aid*  
*Ultrafinish*

*Saftee Cut*  
*Thread Cut Cutting Oils*

*White Kut Soluble Oils*  
*Clean Wheel Coolants*  
*Cost Cut Synthetic Coolants*

*Saw Cut #683*  
*Delta #900 Coolants*  
*XP Rust Preventives*

*Saver Chain & Cable Fluid*  
*Way Oil*  
*Hydraulic Oil*

*Spindle Oil*  
*Compressor Oil*  
*Grease*

*Synthetic Gear Oil*  
*Synthetic Hydraulic Oil*

*Made In U.S.A.*

**Mullen Circle Brand, Inc.**  
**EEZ Products Division**

3514 West Touhy Ave  
Skokie, IL 60076  
847/676-1880

Fax: 847/676-3748

[Solutions@MullenOil.com](mailto:Solutions@MullenOil.com)



*Pure Synthetic for Max Life & Benefit*  
*When You Need The Best*

**Synlube CH Oils** are a family of PAO/Ester synthetic oils intended for use in hydraulic systems and compressors operating in severe environments. These oils exhibit low volatility and low pour points to ensure optimum performance over the entire temperature spectrum.

**Synlube CH Oils** pass 10,000 hours in the turbine oil test (TOST), exhibiting exceptional thermal and oxidative stability. The high viscosity index reduces ambient temperature viscosity, thus enabling faster and more efficient air release.

**Synlube CH Oils** are compatible with petroleum seals and petroleum oils, but mixtures of the two types of fluids will not yield all the benefits of using **Synlube CH Oils** by themselves.

*More ==>*

**...Providing Solutions To Industry Since 1912...**

# Mullen Circle Brand, Inc.

## EEZ PRODUCTS DIVISION

3514 W. Touhy Avenue  
Skokie, IL 60076

Phone 847/676-1880

Fax 847/676-3748

[Solutions@MullenOil.com](mailto:Solutions@MullenOil.com)

## EEZ PRODUCTS SYNLUBE CH SYNTHETIC OILS

	CH-32	CH-46	CH-68	CH-100	CH-150	CH-220
<b>Viscosity,</b>						
<b>Cst 40 C</b>	32	46	68	100	150	220
<b>Cst 100 C</b>	5.9	8.3	11.5	15.0	22.0	30.0
<b>ISO Grade</b>	32	46	68	100	150	220
<b>Color</b>	Clear	Clear	Clear	Clear	Clear	Clear
<b>Flash Point, F</b>	460	460	460	460	460	460

	CH-320	CH-460	CH-680	CH-1000	CH-1500
<b>Viscosity,</b>					
<b>Cst 40 C</b>	320	460	680	1000	1500
<b>Cst 100 C</b>	40.0	53.0	76.0	102.0	138.0
<b>ISO Grade</b>	320	460	680	1000	1500
<b>Color</b>	Clear	Clear	Clear	Clear	Clear
<b>Flash Point, F</b>	460	460	460	460	460

*...Providing Solutions To Industry Since 1912...*

**Cutting Fluids \* Industrial Lubricants \* Greases \* Cleaners**

The Information Given Herein Is Believed To Be Reliable, But No Guarantee Is Made Nor Liability Assumed.