

EEZ PRODUCTS

SYNLUBE GW

*Gear & Way Oils
Synthetic PAO/Ester*

For More Info, Visit..

EEZProducts.com

*Foamy Cutting Fluid
Tuf Tap 2-15-T
Insted-A-Led*

*Micro Max
Cool Aid
Ultrafinish*

*Saftee Cut
Thread Cut Cutting Oils*

*White Kut Soluble Oils
Clean Wheel Coolants
Cost Cut Synthetic Coolants*

*Saw Cut #683
Delta #900 Coolants
XP Rust Preventives*

*Saver Chain & Cable Fluid
Way Oil
Hydraulic Oil*

*Spindle Oil
Compressor Oil
Grease*

*Synthetic Gear Oil
Synthetic Hydraulic Oil*

Made In U.S.A.

**Mullen Circle Brand, Inc.
EEZ Products Division**

3514 West Touhy Ave
Skokie, IL 60076
847/676-1880

Fax: 847/676-3748

Solutions@MullenOil.com



100% Synthetic For Max Life & Benefit

Synlube GW Oils are a family of PAO/Ester synthetic gear oils designed for industrial gearing. Where the viscosity is appropriate, these oils can also be used as premium way and bearing lubricants.

Synlube GW Oils provide the ultimate in thermal and oxidative stability in order to achieve dramatically longer drain intervals. In addition, the exceptionally high viscosity index reduces energy consumption by reducing the ambient temperature viscosity.

Synlube GW Oils are engineered for long term use at temperature extremes. The high flash point, low volatility and low pour point make these oils ideal for severe thermal operating environments.

Synlube GW Oils are completely compatible with petroleum seals and petroleum oils, but mixtures of the two types of fluids will not yield all of the benefits of using **Synlube GW Oils** by themselves.

More ==>

...Providing Solutions To Industry Since 1912...

Mullen Circle Brand, Inc.

EEZ PRODUCTS DIVISION

3514 W. Touhy Avenue
Skokie, IL 60076

Phone 847/676-1880

Fax 847/676-3748

Solutions@MullenOil.com

EEZ PRODUCTS SYNLUBE GW SYNTHETIC OILS

	GW-32	GW-46	GW-68	GW-100	GW-150	GW-220
Viscosity,						
Cst 40 C	32	46	68	100	150	220
Cst 100 C	5.9	8.3	11.5	15.0	22.0	30.0
ISO Grade	32	46	68	100	150	220
AGMA Grade		1	2	3	4	5
Color	Clear	Clear	Clear	Clear	Clear	Clear
Flash Point, F	460	460	460	460	460	460
USS 224	Pass	Pass	Pass	Pass	Pass	Pass

	GW-320	GW-460	GW-680	GW-1000	GW-1500
Viscosity,					
Cst 40 C	320	460	680	1000	1500
Cst 100 C	40.0	53.0	76.0	102.0	138.0
ISO Grade	320	460	680	1000	1500
AGMA Grade	6	7	8	8A	9
Color	Clear	Clear	Clear	Clear	Clear
Flash Point, F	460	460	460	460	460
USS 224	Pass	Pass	Pass	Pass	Pass

***** Cross Reference *****

Synlube GW-32 = Mobil SHC 624

Synlube GW-68 = Mobil SHC 626

Synlube GW-320 = Mobil SHC 632

Synlube GW-460 = Mobil SHC 634

Synlube GW-100 = Mobil SHC 627

Synlube GW-150 = Mobil SHC 629

Synlube GW-680 = Mobil SHC 636

Synlube GW-1000 = Mobil SHC 639

Synlube GW-220 = Mobil SHC 630

...Providing Solutions To Industry Since 1912...

Cutting Fluids * Industrial Lubricants * Greases * Cleaners

The Information Given Herein Is Believed To Be Reliable, But No Guarantee Is Made Nor Liability Assumed.