SAFETY DATA SHEET

***** SECTION I – IDENTIFICATION *****

MANUFACTURER NAME Mullen Circle Brand, Inc. EEZ Products Division 3514 West Touhy Avenue Skokie, Illinois 60076		PHONE NUME	847/676-1880
PRODUCT NAME	Ultrafinish		
RECOMMENDED USE	Lubricant	E-Mail	SDS@MullenOil.com
RESTRICTIONS ON USE	It is against federal law t	o use this product i	inconsistent with its labeling
***** S	ECTION II – HAZARD	(S) IDENTIFICA	TION ****
OSHA Classification	Hazardous		
GHS HAZARD CLASS Physical Hazards	Not classified		
Health Hazards	Serious eye damage/eye irritation – Category 2b Repr. toxicity – Effects on or via lactation		
Environmental Hazards Hazardous to the aquatic environment, acute and long term hazard, Category 1			
GHS Symbol/Pictogram	¥2		
Signal Word	Warning		
Hazard Statements	Causes eye irritation May cause harm to breas Very toxic to aquatic life		effects

PRODUCT NAME

***** SECTION II - HAZARD(S) IDENTIFICATION (continued) *****

Precautionary Statements Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not eat, drink or smoke when using this product Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Avoid breathing dust, fumes, gas, mist, vapors, spray Wash thoroughly after handling Wear protective gloves, protective clothing, eye protection, face protection
Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician Do not induce vomiting IF ON SKIN: Wash with plenty of water IF ON SKIN (or hair): Remove contaminated clothing. Rinse skin with water If skin irritation occurs, get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention IF INHALED: Remove person to fresh air and keep comfortable for breathing Call a POISON CENTER/doctor/physician if you feel unwell Avoid contact during pregnancy and while nursing Specific treatment (see first aid section) In case of fire: Use foam, CO2, dry chemical
Storage	Store in a well ventilated place. Keep container closed when not in use Keep cool Store locked up
Disposal	Dispose of contents/container in accordance with local/state/federal regulations Avoid release to the environment

***** SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS *****

Substance MixtureX		
Chemical Name	CAS#	%
Highly Refined Petroleum Oils *	64742-52-5 64742-54-7	40-50%
Chloro-alkanes, C14-C16	63449-39-8	40%
Glycol Ether DB	112-34-5	1-5%

* Hazardous only if misted

***** SECTION IV - FIRST AID MEASURES *****

Description Of Necessary First Aid Measures

Eye Contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Get medical attention.

Skin Contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth to mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Ingestion

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

***** SECTION V - FIREFIGHTING MEASURES *****

Extinguishing Media

Suitable

Foam, CO2, dry chemicals, water fog or mist.

Unsuitable

Do not use water jet.

Specific Hazards

In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous Decomposition Products

Oxides of carbon, sulfur. Hydrogen chloride.

Special Precautions – Fire Fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if it can be done without risk. No action shall be taken involving any personal risk or without suitable training.

Special Protective Equipment – Fire Fighters

Wear positive pressure self-contained breathing apparatus (SCBA) and full protective clothing.

***** SECTION VI - ACCIDENTAL RELEASE MEASURES *****

Personal Precautions, Protective Equipment And Emergency Procedures

For Non-Emergency Personnel

Take no action involving personal risk without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery, use care to avoid falling.

For Emergency Responders

If specialized clothing is required to deal with the spillage, take note of any information in Section VIII on suitable and unsuitable materials. See also the information in "For Non-Emergency Personnel".

Environmental Precautions

Avoid dispersal of spilled products and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product causes environmental pollution.

Methods And Materials For Containment And Cleaning Up

Small Spill

Stop leak if without risk. Eliminate ignition sources. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spill

Stop leak if without risk. Eliminate ignition sources. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with noncombustible, absorbent material and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

***** SECTION VII - HANDLING & STORAGE *****

Precautions For Safe Handling

Protective Measures

Put on appropriate personal protective equipment (See Section VIII). Do not swallow. Avoid contact with eyes, skin, clothing. Avoid breathing vapor and mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice On General Occupational Hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section VIII for additional information on hygiene measures.

Conditions For Safe Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see Section X) and food and drink. Keep away from heat, sparks and open flame. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

***** SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION *****

Exposure Limits

Ingredient Name	Exposure Limits	
Highly Refined Petroleum Oil *	ACGIH TLV-TWA NIOSH STEL NIOSH TWA OSHA PEL-Ceiling	5 mg/m3 As Mist; 8 Hours 10 mg/m3 As Mist 5 mg/m3 As Mist 5 mg/m3 as Mist
Chloro-alkanes, C14-C16	Not established	
Glycol Ether DB	ACGIH TLV-TWA	10 ppm

* Hazardous only if misted

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

Hygiene Measures

Wash hands, forearms and face thoroughly after handling chemical products and before eating, smoking or using the lavatory as well as at the end of the work period. Wash contaminated clothing before reusing.

Respiratory Protection

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Eye Protection

Safety glasses equipped with side shields in conjunction with a face shield are recommended in industrial settings.

Skin Protection

Wear impervious protective gloves. Wear protective gear as needed - apron, suit, boots.

***** SECTION IX - PHYSICAL & CHEMICAL PROPERTIES *****

Appearance Physical State Color	Liquid Gold
Odor Odor Threshold	Mild hydrocarbon Not available
Ph Melting Point Freezing Point (Pour Point)	None 0 F 0 F
Initial Boiling Point Boiling Range	>600 F >600 F
Drop Point Flash Point	Not applicable >390

***** SECTION IX - PHYSICAL & CHEMICAL PROPERTIES (continued) *****

Evaporation Rate Explosive Limits Upper Lower	Does not evaporate Not available Not available
Vapor Pressure	Not available
Vapor Density	Not available
Specific Gravity	1.07
Density	8.8 Pounds/gallon
Solubility	Not soluble in water
Auto Ignition Temperature	>600 F
Decomposition Temperature	Not available
Viscosity	400 SUS @ 100 F (est.)
Partition coefficient (n-octanol/water)	Not available
Volatile Organic Compounds	0%, wt% (LVP)

***** SECTION X - STABILITY & REACTIVITY

Reactivity

Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS definitions

Chemical Stability

This product is stable under normal conditions.

Possibility Of Hazardous Reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions To Avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible Materials

Reactive or incompatible with the following materials: Strong oxidizing agents.

Hazardous Decomposition Products

Oxides of carbon and sulfur. Hydrogen chloride.

Primary Routes Of Exposure:	Eye contact, Ingestion, Inhalation, Skin contact	
Acute Toxicity:	Not acutely toxic	
Information On Toxicological Effects - Effects Of Overexposure		
Inhalation	Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression).	
Skin Contact	Causes mild skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.	
Eye Contact	Contact with the eye causes irritation. May cause tearing, redness and discomfort.	
Ingestion	This material may be harmful if swallowed or liquid is aspirated into lungs. Ingestion may cause gastrointestinal tract irritation. May cause diarrhea.	
Chronic Hazards	Defatting of the skin.	
Sensitization Respiratory	Not classified	
Skin Sensitization	Not classified	
Germ Cell Mutagenicity	Non-mutagenic based on Modified Ames Assay	
Carcinogenicity	Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346. This product is not listed as a carcinogen by IARC, OSHA, NTP.	
Fertility Effects	May cause harm to breast-fed children	
Specific Target Organ Toxicity Single Exposure	Not classified	
Repeated Exposure	Not classified	
Aspiration Hazard	Not classified	

***** SECTION XI - TOXICOLOGICAL INFORMATION *****

PRODUCT NAME

Mullen Circle Brand, Inc. EEZ Products Division Ultrafinish

***** SECTION XII - ECOLOGICAL INFORMATION *****

Ecotoxicity

Not available

Persistence & Degradability

Not available

Bioaccumulative Potential

Not available

Mobility In Soil Not available

Other Adverse Effects

Very toxic to aquatic life with long lasting effects.

***** SECTION XIII - DISPOSAL CONSIDERATIONS *****

Disposal Methods

Waste generation should be avoided or minimized wherever possible. Dispose of in accordance with federal, state, and local regulations. After the container has been emptied, it may contain hazardous residues. Avoid sparks and open flame. Do not cut, puncture, or weld on or near the container. Do not reuse the container for any purpose until properly reconditioned.

RCRA Classification

UN#

Not a hazardous waste

***** SECTION XIV - TRANSPORT INFORMATION *****

DOT

Not regulated

DescriptionPetroleum oil, nosTransport Hazard classNonePacking GroupNone

Mullen Circle Brand, Inc. EEZ Products Division Ultrafinish

***** SECTION XV – REGULATORY INFORMATION *****

TSCA Section 12(b) Export notification (40 CFR 707 Subpart D): None			
CERCLA Hazardous Substance List (40 CFR 3	302.4): Not listed		
US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed			
SARA Section 302 – Threshold Planning Quant	ity : None		
SARA Title III – Section 311/312			
Immediate/Acute Health Effects	: Yes		
Fire Hazard	: No		
Delayed/Chronic Health Effects	: Yes		
Reactivity Hazard	: No		
Sudden Release Of Pressure Hazard	: No		
Chemical Release Reporting:			
SARA Section 313	: Not listed		
CERCLA	: Not listed		
TSCA Inventory	: All product ingredients are listed on the chemical inventory.		
Clean Air Act			
Ozone Depleting Compounds	: No		

***** SECTION XVI - OTHER INFORMATION *****

The above mentioned information is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition the person receiving it shall make his own determination as to the suitability of the material for his particular use and on the condition he assume the risk of his use thereof.

HMIS HAZARD CLASS:

Health	1 (Slight)
Fire	1 (Slight)
Reactivity	0 (Least)
Personal Protection	В

Revision Date: January 1, 2017